



## 8-Port 10/100/1000Mbps PoE Switch with 1 Gigabit RJ45 and 1 Gigabit SFP Uplink



SP5200-8PGE1GE1GF-DC

### Key Features:

**Ports:** Provide 8\*10/100/1000Mbps PoE ports and 1 \*1.25Gbps RJ45 and 1 Gigabit SFP Uplink

**PoE Standard:** IEEE802.3af/at Power over Ethernet (PoE) Compliant

**Total Power:** Total power budget of 96W and 30W for all single PoE ports

**Self-adaption:** RJ45 port supports 10/100/1000Mbps Auto MDI/MDIX

**Wide Application:** Designed for Wifi AP and IP Security camera.VoIP etc

**Surge protection:** Protect the device from lighting surges and others electrical hazards

**Considerate Design:** Exquisite compact size with fanless design

**Easy to use:** Plug and play, No configuration required

### Versatile PoE Port

Featuring 8\* 10/100/1000Mbps PoE ports which support IEEE802.3af/at standard and 1 Gigabit RJ45 and 1\* 1.25Gbps SFP Uplink ports. the Benchu Group PoE switch provides Maximun power budget of 96W and 30W for single PoE ports sepectively,allowing users to have several different Networking products configured



### 1 Gigabit SFP Uplink Port

With 1 SFP module slot available, the SFP uplink port is ideal for connecting the switch to the network's backbone, providing more than enough bandwidth and stability for ultra high speed data transferring, Beside the SFP can transmette the date with Max 100Km distance with more economic solution

### Surge Protection Design

Reaching 6KV surge protection, the PoE ports owns the capacity to keep the PoE Switch from lightning strikes and other electrical surges, offering more reliable performance even in some harsh environments.



# SP5200-8PGE1GE1GF-DC

8-Port 10/100/1000M PoE Switch with 1 Gigabit RJ45 and 1 Gigabit SFP Uplink


## Technical Datasheet

Model	SP5200-8PGE1GE1GF-DC	
Hardware Specifications		
Network Connector	9* 10/100/1000BASE-T RJ45 auto MDI/MDIX ports 1* 1000BASE-X SFP	
PoE Port	8 10/100/1000Mbps POE PSE port	
LED indicators	Power Indicator: PWR(green). Network Indicator: Link(green). PoE Working Indicator: PoE(green)	
Switch Architecture	Store and Forward	
Transmission model	IEEE802.3X full-duplex and Backpressure half-duplex	
Switch Performance	Backplane bandwidth	24Gbps
	Packet forwarding rate	17.86Mpps
	MAC address	8k
Power requirement	AC100-240V 50/60Hz	
ESD Protection	6KV ESD	
Dimension(WxDxH)	210mm x 98mm x 30mm(8.27in x3.86in x 1.18in)	
Weight	0.8Kg	
Power over Ethernet (PoE) Specifications		
Network standard	IEEE802.3i 10 BASE-T	
	IEEE802.3u 100 BASE-TX	
	IEEE 802.3ab Gigabit 1000BASE-T	
	IEEE 802.3z Gigabit 1000BASE-T	
	IEEE802.3x Flow Control	
	IEEE802.3af Power over Ethernet	
	IEEE802.3at Power over Ethernet	
	IEEE802.3az EEE	
PoE Standard	IEEE 802.3af Power over Ethernet/PSE	
	IEEE 802.3at Power over Ethernet Plus/PSE	
PoE Supply Type	1/2(+), 3/6(-) End-span	
PoE Power Output	Per Port 52V DC, 300mA. max. 15.4 watts (IEEE 802.3af)	
	Per Port 52V DC, 600mA. max. 30 watts (IEEE 802.3at)	
PoE Power budget	96W	
Environment		
Safety	FCC Part15 Class A,CE,RoHs	
Environment specification	Operating temperature: -20℃~55℃， operating humidity: 5%~95%	
	Storage temperature: -20℃~75℃， storage humidity: 5%~95%	


# SP5200-8PGE1GE1GF-DC

8-Port 10/100/1000M PoE Switch with 1 Gigabit RJ45 and 1 Gigabit SFP Uplink


## Interfaces



## Structure Diagrams



## Applications



## Ordering Information

SP5200-8PGE1GE1GF-DC

8 Ports 10/100/1000Mbps PoE switch with 1 Gigabit RJ45 and 1 Gigabit SFP Uplink, 6KV surge protection, IEEE802.3af/at